

COMP MOUNT



Simple 3-Piece Design Watertight For Life



Pegasus solar's comp mounts are a cost effective, high-quality option for rail installations on composition shingle roofs. Designed to last decades, the one-piece flashing with elevated cone means there is simply nothing to fail.



25-Year Warranty

Manufactured with advanced materials and coatings to outlast the roof itself



Code Compliant

Fully IBC/CBC Code Compliant Exceeds ASCE 7-16 Standards



Superior Waterproofing

Tested to AC286 without sealant Water seal elevated 0.9" above



All-In-One Kit Packaging

Flashings, L-Feet and SS lags with bonded EPDM washers are included in each 24-pack



COMP MOUNT

1 Drill pilot hole in the center of the rafter.



2Optional: Apply a
"u-shape" of sealant to
the underside of the
flashing and position
under 2nd shingle
course, cone over
pilot hole.



3Place L-Foot over cone and install lag with washer through L-Foot.





4Drive lag to required depth. Attach rail per rail manufacturer's instructions.



1,5" 3.5"









SPECIFICATIONS	COMP MOUNT INSTALL KITS				
SKU	PSCR-CBB0	PSCR-UBB0	SPCR-CBBH	PSCR-CMM0	PSCR-UMM0
Finish	Black L-Foot And Black Flashing			Mill	
L-Foot Type	Closed Slot	Open Slot	Closed Slot	Closed Slot	Open Slot
Kit Contents	L-Foot, Flashing, 5/16" x 4 1/2" SS Lag with metalized EPDM washer	L-Foot, Flashing, 5/16" x 4 1/2" SS Lag with metalized EPDM washer and M10 Hex Bolt	L-Foot, Flashing, 5/16" x 4 1/2" SS Lag with metalized EPDM washer	L-Foot, Flashing, 5/16" x 4 1/2" SS Lag with metalized EPDM washer	L-Foot, Flashing, 5/16" x 4 1/2" SS Lag with metalized EPDM washer
Roof Type	Composition Shingle				
Certifications	IBC, ASCE/SEI 7-16, AC286				
Install Application	Railed Systems				
Compatible Rail	Most				
Flashing Material	Painted Galvalume Plus			Galvalume Plus	
L-Foot Material	Aluminum				
Kit Quantity	24				
Boxes per Pallet	72				

Patents pending. All rights reserved. ©2021 Pegasus Solar